

View Online at <https://aerobasegroup.com/nsn/4820-00-060-3203>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Maximum Operating Temp:**

275.0 degrees fahrenheit single response

**End Application:**

Acft, type f-4; t.O. 1f-4c-4-3, fig 104, ind 18

**Connection Style:**

Flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

12 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

1.062 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Special Features:**

Outlet end bulkhead per ms33657, angle of valve is 45 degrees

**Material:**

Stainless steel

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base single response

**Surface Treatment:**

Passivate

**Style Designator:**

Angle

**Supplementary Features:**

Nha ref no. 53-69724 ()

**Thread Series Designator:**

Unj 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A530b0