NSN 4820-00-060-3204



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-060-3204 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** Flared (tube) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 2nd end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 20 2nd end **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 2nd end **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Material: Steel comp 440a flow control device **Material Specification:** Qq-a-225/6, alloy 2024, t4 federal specification single material response seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Straight thru

Unf 2nd end Shelf Life:

N/a

Thread Series Designator:

NSN 4820-00-060-3204

Check Valve - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A530b0