NSN 4820-00-060-5871

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-060-5871

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

50.0 pounds per square inch single response

Thread Size:

0.375 inches all ends

Seat Angle:

37.0 degrees all ends

Outside Diameter Tube Accommodated:

0.188 inches all ends

Material:

Aluminum alloy

Material Specification:

Qq-a-225/6, alloy 2024, t4 federal specification single material response

Media For Which Designed:

Air single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Test Data Document:

99240-96c standard (includes industry or association standards, individual manufactureer standards, etc.).

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

NSN 4820-00-060-5871

Check Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0

