NSN 4820-00-060-7233

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-060-7233

Pipe Size Accommodated:

0.750 inches 2nd end

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 2nd end

Features Provided:

Pressure tight outlet side

Adjustable Pressure Range:

+1.0/+250.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Opening Pressure Setting:

25.0 pounds per square inch

Material:

Copper alloy

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Angle

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-00-060-7233

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

