NSN 4820-00-066-2358

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-066-2358

Pipe Size Accommodated:
2.000 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
500.0 degrees fahrenheit 1st response
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Maximum Operating Pressure:
230.0 pounds per square inch 2nd response
Outside Diameter:
6.000 inches 1st end
Face To Face Distance:
8.000 inches
Thickness:
0.625 inches 1st end
Bolt Hole Diameter:
0.625 inches 1st end
Bolt Circle Diameter:
4.750 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:
Straight through flanged ends

NSN 4820-00-066-2358

Globe Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0