NSN 4820-00-066-2359

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-066-2359

Flow Control Device:
Disk
Bonnet Type:
Exposed spring Pennet Attachment Methods
Bonnet Attachment Method:
Bolted Dick Loading Mathods
Disk Loading Method:
Spring Mayimum Operating Towns
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round 1st end
Connection Type:
Flange 1st end
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
900.0 pounds per square inch single response
Opening Pressure Setting:
900.0 pounds per square inch
Outside Diameter:
7.500 inches 2nd end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.625 inches 1st end
Raised Face Diameter:
5.000 inches 2nd end
Special Features:
1st connection face to center line distance5.562 in. 2nd connection face to centerlinedistance 6.250 in.
Material:
Stainless steel seat
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-00-066-2359

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0