# NSN 4820-00-066-9011

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-066-9011

Pipe Size Accommodated:

1.000 inches 1st end

**Thread Direction:** 

Right-hand 1st end

# Flow Control Device:

Poppet

# Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Threaded

# **Disk Loading Method:**

Spring

#### Valve Discharge Flow Rate:

170.0 cubic feet per minute

#### Maximum Operating Temp:

406.0 degrees fahrenheit single response

#### **Connection Style:**

Plain (pipe) 1st end

# Valve Operation Method:

Automatic or manual

# **Connection Type:**

Threaded external pipe 1st end

# **Features Provided:**

Valve stem lock shield

#### Maximum Operating Pressure:

250.0 pounds per square inch single response

# Thread Size:

1.000 inches 1st end

#### **Opening Pressure Setting:**

85.0 pounds per square inch

#### Material:

Steel stem

#### **Material Specification:**

Qq-c-390, alloyb5/d/ federal specification single material response body

#### Media For Which Designed:

Fuel/oil, hydrocarbon single response

#### Style Designator:

Straight thru

# **Thread Series Designator:**

Npt 1st end

# Shelf Life:

N/a

# NSN 4820-00-066-9011

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

