NSN 4820-00-068-6915

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-068-6915

| Pipe Size Accommodated: |
|---|
| 0.500 inches all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Bolted |
| Renewable Seat Ring Type: |
| Pressed-in |
| Maximum Operating Temp: |
| 775.0 degrees fahrenheit single response |
| Connection Style: |
| Beveled (pipe) all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Butt weld pipe all ends |
| Features Provided: |
| Bonnet packing |
| Maximum Operating Pressure: |
| 600.0 pounds per square inch 2nd response |
| Material: |
| Steel uns k03504 body |
| Material Specification: |
| Qq-s-763 federal specification single material response stem |
| Media For Which Designed: |
| Water-oil-gas 1st response |
| Style Designator: |
| Straight thru |
| Reference Number Differentiating Characteristics: |
| As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |