## NSN 4820-00-068-6915

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-068-6915

| Pipe Size Accommodated:   |
|---|
| 0.500 inches all ends   |
| Flow Control Device:  |
| Disk  |
| Bonnet Type:  |
| Inside screw  |
| Bonnet Attachment Method:   |
| Bolted  |
| Renewable Seat Ring Type:   |
| Pressed-in  |
| Maximum Operating Temp:   |
| 775.0 degrees fahrenheit single response  |
| Connection Style:   |
| Beveled (pipe) all ends   |
| Valve Operation Method:   |
| Manual  |
| Connection Type:  |
| Butt weld pipe all ends   |
| Features Provided:  |
| Bonnet packing  |
| Maximum Operating Pressure:   |
| 600.0 pounds per square inch 2nd response   |
| Material:   |
| Steel uns k03504 body   |
| Material Specification:   |
| Qq-s-763 federal specification single material response stem  |
| Media For Which Designed:   |
| Water-oil-gas 1st response  |
| Style Designator:   |
| Straight thru   |
| Reference Number Differentiating Characteristics:   |
| As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A046b0  |