NSN 4820-00-068-7773

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-068-7773 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 43.0 gallons per minute **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 12 all ends **Adjustable Pressure Range:** +2300.0 to 3850.0 pounds per square inch **Maximum Operating Pressure:** 6000.0 pounds per square inch single response **Thread Size:** 1.062 inches all ends **Outside Diameter Tube Accommodated:** 0.750 inches all ends Hydraulic fluid, petroleum base single response

Material: Stainless steel seat Media For Which Designed: **Style Designator:** Straight thru **Thread Series Designator:** Un all ends Shelf Life: N/a **Unit Of Measure:**

NSN 4820-00-068-7773

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0