## NSN 4820-00-068-7773

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-068-7773

Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
43.0 gallons per minute
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
12 all ends
Adjustable Pressure Range:
+2300.0 to 3850.0 pounds per square inch
Maximum Operating Pressure:
6000.0 pounds per square inch single response
Thread Size:
1.062 inches all ends
Outside Diameter Tube Accommodated:
0.750 inches all ends
Material:
Stainless steel seat
Media For Which Designed:
Hydraulic fluid, petroleum base single response
Style Designator:
Straight thru
Thread Series Designator:
Un all ends
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 4820-00-068-7773

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

