## NSN 4820-00-068-8991

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-068-8991 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Packing retaining **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 4.0 cubic feet per minute **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end **Features Provided:** Pressure tight outlet side Adjustable Pressure Range: +49.0 to 51.0 pounds per square inch **Maximum Operating Pressure:** 50.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end Material: Aluminum alloy Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Straight thru **Thread Series Designator:** Unjf 1st end Shelf Life:

N/a
Unit Of Measure:

## NSN 4820-00-068-8991

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0