NSN 4820-00-068-8991

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-068-8991

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Packing retaining

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

4.0 cubic feet per minute

Maximum Operating Temp:

275.0 degrees fahrenheit 2nd response

Connection Style:

Gasket sea (boss) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss 1st end

Features Provided:

Pressure tight outlet side

Adjustable Pressure Range:

+49.0 to 51.0 pounds per square inch

Maximum Operating Pressure:

50.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Material:

Aluminum alloy

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-00-068-8991

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

