## NSN 4820-00-071-4840

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-071-4840

Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
6485.0 cubic feet per minute
Bolt Hole Quantity:
8 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
600.0 pounds per square inch single response
Opening Pressure Setting:
595.0 pounds per square inch
Outside Diameter:
7.000 inches 2nd end
Bolt Hole Diameter:
0.750 inches 2nd end
Bolt Circle Diameter:
5.500 inches 2nd end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
3.500 inches 1st end
Special Features:
1st connection face to center line distance 5.500 in. 2nd connection face to centerline distance 5.000
Material:
Steel
Style Designator:
Angle

## NSN 4820-00-071-4840

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

