## NSN 4820-00-072-0579

Safety Relief Valve - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/4820-00-072-0579

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st endplain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st endthreaded internal pipe 2nd end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+10.0/+400.0 pounds per square inch
Maximum Operating Pressure:
2500.0 pounds per square inch 1st response
Thread Size:
0.500 inches 2nd end
Opening Pressure Setting:
50.0 pounds per square inch
Material:
Copper alloy
Media For Which Designed:
Air 1st responseacetylene 2nd responseammonia, gaseous 3rd responserefrigerant 12 4th responsehydrogen 5th response
Style Designator:
Straight through note: to be used for valve bodies of separable sections.
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

## NSN 4820-00-072-0579

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0