

View Online at <https://aerobasegroup.com/nsn/4820-00-073-2255>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Minimum Operating Temp:

-65.0 degrees fahrenheit

Connection Style:

Plain (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Adjustable Pressure Range:

+10.0/+30.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Opening Pressure Setting:

20.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Steel comp 303 seat

Material Specification:

Fedstd66, aisi303/sae30303 federal standard single material response body

Media For Which Designed:

Nitrogen, gaseous 5th response

Surface Treatment:

Passivate

Style Designator:

Straight through w/baffle

Thread Series Designator:

Unjf 1st end

Furnished Items And Quantity:

1 deflector cap

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0