## NSN 4820-00-073-2634

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-073-2634

Thread	Class:

3a 1st end

**Thread Direction:** 

Right-hand 1st end

## Flow Control Device:

Poppet

## **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

250.0 degrees fahrenheit single response

**Connection Style:** 

Flareless 2nd end

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded external tube 2nd end

**Mounting Position:** 

Horizontal or vertical

## Maximum Operating Pressure:

3000.0 pounds per square inch single response

## Thread Size:

0.875 inches 1st end

#### Seat Angle:

12.0 degrees 2nd end

#### Outside Diameter Tube Accommodated:

0.625 inches 1st end

#### Material:

Steel comp 303

#### **Material Specification:**

66 federal standard single material response

#### Media For Which Designed:

Hydraulic fluid, mineral base single response

#### Surface Treatment:

Passivate

#### Style Designator:

Angle

## Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 4820-00-073-2634

Check Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A530b0

