NSN 4820-00-073-8753

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-073-8753 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Disk Loading Method:** Spring Valve Discharge Flow Rate: 5.0 gallons per minute **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Manual **Connection Type:** Threaded internal boss 1st end **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 18 1st end Adjustable Pressure Range: +3100.0 to 3400.0 pounds per square inch **Maximum Operating Pressure:** 3400.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end **Opening Pressure Setting:** 3400.0 pounds per square inch Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No Fiig: A046b0

NSN 4820-00-073-8753

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.