

View Online at <https://aerobasegroup.com/nsn/4820-00-073-9155>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Connection Style:

Flared (tube) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 2nd end

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

12 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Outside Diameter Tube Accommodated:

0.750 inches 1st end

Material:

Stainless steel

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Passivate

Style Designator:

Straight thru

Test Data Document:

99240-2c5938 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0