

NSN 4820-00-074-1298 Fluid Pressure Regulating Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-074-1298 **Body Material:** Aluminum, mil&a&8625 **Outside Surface Treatment:** Anodized, mil-a-8625 **Body Style:** Straight thru Stem Material: Steel, qq-s-763, class 440c Media For Which Designed: Hydrocarbon fuels and oils **First End Connection Type:** Threaded internal boss First End Style Designator: Gasket seal First End Thread Size And Series/type Designator: 7/16-20 unf First End Thread Class: 3b **First End Thread Direction:** Right-hand **Second End Relationship With First End:** Identical **Seat Material:** Steel, qq-s-763, class 440c **Center To Center Distance:** 1.500 inches **Flow Control Device:** Ball

Flow Control Device Material:

Steel, stainless, class 440c

End Connection Quantity:

Mounting Facility:

Bracket

Regulation Type:

Manual, double stage

Manual Control Method:

Lever

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

4500.0 pounds per square inch

NSN 4820-00-074-1298

Fluid Pressure Regulating Valve - Page 2 of 2



Outlet Pressure Setting:

3000.0 pounds per square inch

Filter:

Not included

Tempurature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A21100