## NSN 4820-00-075-2380

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-075-2380

3a all ends Thread Direction: Right-hand all ends Flow Control Device: Poppet Maximum Operating Temp: 500.0 degrees fahrenheit single response Connection Style: Swivel nut, compression (tube) all ends Valve Operation Method: Automatic Connection Type: Threaded internal tube all ends Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator: Unf all ends	Thread Class:
Right-hand all ends Flow Control Device: Poppet Maximum Operating Temp: 500.0 degrees fahrenheit single response Connection Style: Swivel nut, compression (tube) all ends Valve Operation Method: Automatic Connection Type: Threaded internal tube all ends Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	3a all ends
Flow Control Device: Poppet  Maximum Operating Temp: 500.0 degrees fahrenheit single response  Connection Style: Swivel nut, compression (tube) all ends  Valve Operation Method: Automatic  Connection Type: Threaded internal tube all ends  Mounting Facility: Threaded fastener  Mounting Position: Horizontal  Valve Size: 0.750 inches  Thready Qty Per Inch (tpi): 16 all ends  Maximum Operating Pressure: 100.0 pounds per square inch single response  Thread Size: 0.750 inches all ends  Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends  Thread Series Designator:	Thread Direction:
Maximum Operating Temp: 500.0 degrees fahrenheit single response Connection Style: Swivel nut, compression (tube) all ends Valve Operation Method: Automatic Connection Type: Threaded internal tube all ends Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Right-hand all ends
Maximum Operating Temp: 500.0 degrees fahrenheit single response Connection Style: Swivel nut, compression (tube) all ends Valve Operation Method: Automatic Connection Type: Threaded internal tube all ends Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Straight through flanged ends Thread Series Designator:	Flow Control Device:
Connection Style: Swivel nut, compression (tube) all ends Valve Operation Method: Automatic Connection Type: Threaded internal tube all ends Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Straight through flanged ends Thread Series Designator:	Poppet
Connection Style: Swivel nut, compression (tube) all ends Valve Operation Method: Automatic Connection Type: Threaded internal tube all ends Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Maximum Operating Temp:
Swivel nut, compression (tube) all ends  Valve Operation Method: Automatic  Connection Type: Threaded internal tube all ends  Mounting Facility: Threaded fastener  Mounting Position: Horizontal  Valve Size: 0.750 inches  Thready Qty Per Inch (tpi): 16 all ends  Maximum Operating Pressure: 100.0 pounds per square inch single response  Thread Size: 0.750 inches all ends  Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Straight through flanged ends  Thread Series Designator:	500.0 degrees fahrenheit single response
Valve Operation Method: Automatic Connection Type: Threaded internal tube all ends Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Straight through flanged ends Thread Series Designator:	Connection Style:
Automatic  Connection Type: Threaded internal tube all ends  Mounting Facility: Threaded fastener  Mounting Position: Horizontal  Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends  Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends  Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends Thread Series Designator:	Swivel nut, compression (tube) all ends
Connection Type: Threaded internal tube all ends Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Valve Operation Method:
Threaded internal tube all ends  Mounting Facility: Threaded fastener  Mounting Position: Horizontal  Valve Size: 0.750 inches  Thready Qty Per Inch (tpi): 16 all ends  Maximum Operating Pressure: 100.0 pounds per square inch single response  Thread Size: 0.750 inches all ends  Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends  Thread Series Designator:	Automatic
Mounting Facility: Threaded fastener Mounting Position: Horizontal Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Connection Type:
Threaded fastener  Mounting Position: Horizontal  Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends  Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends  Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends Thread Series Designator:	Threaded internal tube all ends
Mounting Position: Horizontal  Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends  Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Mounting Facility:
Valve Size: 0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Threaded fastener
Valve Size:  0.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Mounting Position:
O.750 inches Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Horizontal
Thready Qty Per Inch (tpi): 16 all ends  Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends Thread Series Designator:	Valve Size:
Maximum Operating Pressure: 100.0 pounds per square inch single response Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches Outside Diameter Tube Accommodated: 0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	0.750 inches
Maximum Operating Pressure:  100.0 pounds per square inch single response Thread Size:  0.750 inches all ends Face To Face Distance:  3.000 inches Outside Diameter Tube Accommodated:  0.500 inches all ends Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Thready Qty Per Inch (tpi):
Thread Size: 0.750 inches all ends Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends Thread Series Designator:	16 all ends
Thread Size:  0.750 inches all ends  Face To Face Distance:  3.000 inches  Outside Diameter Tube Accommodated:  0.500 inches all ends  Material:  Stainless steel  Media For Which Designed:  Ethylene glycol single response  Surface Treatment:  Passivate  Style Designator:  Straight through flanged ends  Thread Series Designator:	Maximum Operating Pressure:
0.750 inches all ends  Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends  Thread Series Designator:	100.0 pounds per square inch single response
Face To Face Distance: 3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends Thread Series Designator:	Thread Size:
3.000 inches  Outside Diameter Tube Accommodated: 0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response  Surface Treatment: Passivate  Style Designator: Straight through flanged ends Thread Series Designator:	0.750 inches all ends
Outside Diameter Tube Accommodated:  0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Face To Face Distance:
0.500 inches all ends  Material: Stainless steel  Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	3.000 inches
Material: Stainless steel Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Outside Diameter Tube Accommodated:
Stainless steel  Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	0.500 inches all ends
Media For Which Designed: Ethylene glycol single response Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Material:
Ethylene glycol single response  Surface Treatment:  Passivate  Style Designator:  Straight through flanged ends  Thread Series Designator:	Stainless steel
Surface Treatment: Passivate Style Designator: Straight through flanged ends Thread Series Designator:	Media For Which Designed:
Passivate  Style Designator:  Straight through flanged ends  Thread Series Designator:	Ethylene glycol single response
Style Designator: Straight through flanged ends Thread Series Designator:	Surface Treatment:
Straight through flanged ends Thread Series Designator:	Passivate
Thread Series Designator:	Style Designator:
_	Straight through flanged ends
Unf all ends	Thread Series Designator:
	Unf all ends
Shelf Life:	Shelf Life:
	N/a
NI/a	IN/a

## NSN 4820-00-075-2380

Check Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A530b0