NSN 4820-00-076-6292

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-076-6292

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Offset Distance:
0.187 inches
Flow Control Device:
Poppet
Bonnet Type:
Packing retaining
Disk Loading Method:
Spring
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Gasket seal (boss) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded internal boss 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
24 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.375 inches 1st end
Center To Center Distance:
2.313 inches
Outside Diameter Tube Accommodated:
0.187 inches 1st end
Material:
Steel seat
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-076-6292

Lift-check Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A530b0