# NSN 4820-00-076-6292

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-076-6292

Thread	Class:

3b 1st end

**Thread Direction:** 

Right-hand 1st end

# Offset Distance:

0.187 inches

### Flow Control Device:

Poppet

#### Bonnet Type:

Packing retaining

### Disk Loading Method:

Spring

#### Maximum Operating Temp:

160.0 degrees fahrenheit single response

#### **Connection Style:**

Gasket seal (boss) 1st end

# Valve Operation Method:

Manual

### **Connection Type:**

Threaded internal boss 1st end

#### **Mounting Position:**

Horizontal or vertical

## Thready Qty Per Inch (tpi):

24 1st end

#### Maximum Operating Pressure:

3000.0 pounds per square inch single response

### Thread Size:

0.375 inches 1st end

#### **Center To Center Distance:**

2.313 inches

#### **Outside Diameter Tube Accommodated:**

0.187 inches 1st end

#### Material:

Steel seat

#### Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

# Thread Series Designator:

Unf 1st end

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 4820-00-076-6292

Lift-check Valve - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A530b0

