## NSN 4820-00-076-8615

Gate Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-076-8615

Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Union Valve Operation Method: Manual Connection Type: Threaded internal pipe Features Provided: Bonnet packing Maximum Operating Pressure And Media For Which Designed: 200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas Thread Size: 0.500 inches Stem Type: Rising Special Features:
Bonnet Attachment Method: Union Valve Operation Method: Manual Connection Type: Threaded internal pipe Features Provided: Bonnet packing Maximum Operating Pressure And Media For Which Designed: 200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas Thread Size: 0.500 inches Stem Type: Rising
Union  Valve Operation Method:  Manual  Connection Type: Threaded internal pipe  Features Provided: Bonnet packing  Maximum Operating Pressure And Media For Which Designed: 200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas  Thread Size: 0.500 inches  Stem Type: Rising
Valve Operation Method:  Manual  Connection Type: Threaded internal pipe  Features Provided: Bonnet packing  Maximum Operating Pressure And Media For Which Designed: 200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas  Thread Size: 0.500 inches  Stem Type: Rising
Manual  Connection Type: Threaded internal pipe  Features Provided: Bonnet packing  Maximum Operating Pressure And Media For Which Designed: 200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas  Thread Size: 0.500 inches  Stem Type: Rising
Connection Type: Threaded internal pipe Features Provided: Bonnet packing Maximum Operating Pressure And Media For Which Designed: 200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas Thread Size: 0.500 inches Stem Type: Rising
Threaded internal pipe  Features Provided:  Bonnet packing  Maximum Operating Pressure And Media For Which Designed:  200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas  Thread Size:  0.500 inches  Stem Type:  Rising
Features Provided: Bonnet packing Maximum Operating Pressure And Media For Which Designed: 200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas Thread Size: 0.500 inches Stem Type: Rising
Bonnet packing  Maximum Operating Pressure And Media For Which Designed:  200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas  Thread Size:  0.500 inches  Stem Type:  Rising
Maximum Operating Pressure And Media For Which Designed: 200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas Thread Size: 0.500 inches Stem Type: Rising
200.0 pounds per square inch steam and 400.0 pounds per square inch water-oil-gas  Thread Size: 0.500 inches  Stem Type: Rising
Thread Size: 0.500 inches Stem Type: Rising
0.500 inches  Stem Type: Rising
Stem Type: Rising
Rising
•
Special Features:
0.500 in. Pipe size; r.H. Thd; 14 thds per inch; max operating temp 550 degrees f
Material:
Nickel alloy disk
Thread Series Designator:
Npt
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A500a0