NSN 4820-00-078-6587

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:

0.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:

Disk

Bonnet Type: Inside spring



View Online at https://aerobasegroup.com/nsn/4820-00-078-6587

Bonnet Attachment Method:		
Integral		
Disk Loading Method:		
Spring		
Maximum Operating Temp:		
400.0 degrees fahrenheit single response		
Connection Style:		
Plain, optional en (pipe) 1st end		
Valve Operation Method:		
Automatic		
Connection Type:		
Threaded internal pipe 1st end		
Features Provided:		
Pressure tight outlet side		
Thready Qty Per Inch (tpi):		
14 2nd end		
Adjustable Pressure Range:		
+5.0/+250.0 pounds per square inch		
Maximum Operating Pressure:		
250.0 pounds per square inch single respons	e	
Thread Size:		
0.500 inches 2nd end		
Opening Pressure Setting:		
100.0 pounds per square inch		
Material:		
Steel stem		
Style Designator:		
Angle		
Thread Series Designator:		
Npt 1st end		
Reference Number Differentiating Charact	eristics:	
As differentiatedby adsv and end dim. Data		
Shelf Life:		
N/a		

NSN 4820-00-078-6587

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0