NSN 4820-00-078-6592

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-078-6592

Pipe Size Accommodated: 1.000 inches 2nd end Thread Direction: Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Pressure tight outlet side

Thready Qty Per Inch (tpi):

11-1/2 2nd end

Adjustable Pressure Range:

+5.0 to 250.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

1.000 inches 2nd end

Opening Pressure Setting:

50.0 pounds per square inch

Material:

Steel stem

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Reference Number Differentiating Characteristics:

As differentiated by adsv and end dim. Data

Shelf Life:

N/a

NSN 4820-00-078-6592

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

