NSN 4820-00-078-6594

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-078-6594

1.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Adjustable Pressure Range:
+1.0 to 250.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
1.500 inches 2nd end
Opening Pressure Setting:
15.0 pounds per square inch
Material:
Steel stem
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Reference Number Differentiating Characteristics:
As differentiated by pipe size, and thd size and series
Shelf Life:

N/a

NSN 4820-00-078-6594

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0