## NSN 4820-00-080-7799

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-080-7799

| Pipe Size Accommodated:   |
|---|
| 0.500 inches 2nd end  |
| Thread Class:   |
| 3a 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Flow Control Device:  |
| Poppet  |
| Disk Loading Method:  |
| Spring  |
| Maximum Operating Temp:   |
| 180.0 degrees fahrenheit single response                                |
| End Application:  |
| Grumman aircraft model a10  |
| Connection Style:   |
| Plain (pipe) 2nd end  |
| Valve Operation Method:   |
| Automatic   |
| Connection Type:  |
| Threaded external tube 1st end  |
| Mounting Position:  |
| Horizontal or vertical  |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch single response                           |
| Thread Size:  |
| 0.750 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Outside Diameter Tube Accommodated:                                     |
| 0.500 inches 1st end  |
| Material:   |
| Steel comp 304 flow control device                                      |
| Material Specification:   |
| Qq-b-626, alloy 360 federal specification single material response body |
| Media For Which Designed:   |
| Oil, hydraulic single response  |
| Style Designator:   |
| Straight thru   |
| Thread Series Designator:   |
| Unf 1st end   |
| Shelf Life:   |
| N/o   |

## NSN 4820-00-080-7799

Check Valve - Page 2 of 2



|  |  |  | ıre: |
|--|--|--|------|
|  |  |  |      |

--

Demilitarization:

No

Fiig:

A530b0