NSN 4820-00-080-8053

Stop-check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-080-8053

| Pipe Size Accommodated: |
|--|
| 3.000 inches 1st end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Threaded |
| Renewable Seat Ring Type: |
| Pressed-in |
| Maximum Operating Temp: |
| 775.0 degrees fahrenheit single response |
| Connection Style: |
| Beveled (pipe) 1st end |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Butt weld pipe 1st end |
| Mounting Position: |
| Horizontal |
| Maximum Operating Pressure: |
| 600.0 pounds per square inch single response |
| Criticality Code Justification: |
| Zzzy |
| Media For Which Designed: |
| Water-oil-gas single response |
| Style Designator: |
| Straight thru |
| Reference Number Differentiating Characteristics: |
| Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A530b0 |
| |