NSN 4820-00-083-1262

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-083-1262

Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
1.2 gallons per minute
Maximum Operating Temp:
275.0 degrees fahrenheit 2nd response
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
20 all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Opening Pressure Setting:
2800.0 pounds per square inch
Special Features:
Free reverse flow
Material:
Stainless steel stem
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Surface Treatment:
Anodize
Style Designator:
Straight thru
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a

NSN 4820-00-083-1262

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

