## NSN 4820-00-083-1263

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-083-1263 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Packing retaining **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 2.5 gallons per minute **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube all ends **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 4500.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends **Opening Pressure Setting:** 3650.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches all ends Material: Stainless steel flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Straight thru **Thread Series Designator:** Unf all ends Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 4820-00-083-1263

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0