# NSN 4820-00-083-3803

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-083-3803

Flow Control Device:

Disk

**Bolt Hole Quantity:** 

4 2nd end

## Connection Style:

Plain (tube) 1st end

## Width:

3.000 inches 2nd end

#### Length:

3.000 inches 2nd end

## Valve Operation Method:

Automatic

Flange Shape:

Rectangular with holes 2nd end

#### **Connection Type:**

Unthreaded internal tube 1st end

## Maximum Operating Pressure:

7.0 pounds per square inch single response

## **Outside Diameter:**

2.375 inches 2nd end

## Thickness:

0.187 inches 2nd end

## **Bolt Hole Diameter:**

0.259 inches 2nd end

## Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 2nd end

## Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 2nd end

## Flange Face Design:

Raised straight 2nd end

## **Raised Face Height:**

0.187 inches 2nd end

## **Raised Face Diameter:**

2.340 inches 2nd end

## Outside Diameter Tube Accommodated:

1.875 inches 1st end

## **Special Features:**

Mounting position: vertical

## Material:

Steel flow control device

## **Material Specification:**

Qq-a-225/6, alloy 2024 federal specification single material response body

# NSN 4820-00-083-3803

Safety Relief Valve - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-5059 spec.