## NSN 4820-00-087-1583

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-087-1583

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.250 inches 2nd end
Material:
Steel comp 304 flow control device and rubber butadiene-acrylonitrile class nbr flow control device and steel comp 303 flow control device
Material Specification:
66 federal standard single material response body
Media For Which Designed:
Oil single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-087-1583

Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.