NSN 4820-00-089-7677

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-089-7677

| Pipe Size Accommodated: |
|--|
| 2.000 inches all ends |
| Flow Control Device: |
| Disk |
| Maximum Operating Temp: |
| 425.0 degrees fahrenheit 2nd response |
| Connection Style: |
| Streamlined with two brazing ring (pipe) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Unthreaded internal pipe all ends |
| Mounting Position: |
| Horizontal or vertical |
| Maximum Operating Pressure: |
| 400.0 pounds per square inch 2nd response |
| Material: |
| Nickel alloy 400 flow control device or nickel alloy r-405 flow control device or nickel alloy flow control device |
| Material Specification: |
| Astm b164 assn standard 1st material response flow control device or astm b164 assn standard 2nd material response flow control device o |
| qq-n-288 federal standard 3rd material response flow control device |
| Media For Which Designed: |
| Water-oil-gas 2nd response |
| Style Designator: |
| Straight thru |
| Test Data Document: |
| 81349-mil-s-901c/navy specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Reference Number Differentiating Characteristics: |
| As differentiated by 2.000 in. Valve size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A530b0 |
| |
| |