NSN 4820-00-094-8034

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-094-8034

Inread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Piston
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
1.5 gallons per minute
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Adjustable Pressure Range:
+170.0 to 350.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Opening Pressure Setting:
350.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Stainless steel seat
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Surface Treatment:
Anodize
Style Designator:
Angle
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-094-8034

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0