NSN 4820-00-094-8123

Safety Relief Valve - Page 1 of 2

3b all ends

Poppet

Thread Direction:
Right-hand all ends
Flow Control Device:

Disk Loading Method:



View Online at https://aerobasegroup.com/nsn/4820-00-094-8123

Thread Class:

Spring
Valve Discharge Flow Rate:
3.0 gallons per minute
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Mounting Facility:
Threaded fastener
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 all ends
Adjustable Pressure Range:
+300.0 to 725.0 pounds per square inch
Maximum Operating Pressure:
725.0 pounds per square inch single response
Thread Size:
0.562 inches all ends
Opening Pressure Setting:
725.0 pounds per square inch
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Style Designator:
Err-090
Test Data Document:
00502-n20501 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-00-094-8123

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0