NSN 4820-00-097-8172

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-097-8172 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 7.0 gallons per minute **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Valve stem lock shield and pressure tight outlet side **Adjustable Pressure Range:** +1400.0/+2300.0 pounds per square inch **Maximum Operating Pressure:** 2500.0 pounds per square inch single response **Thread Size:** 0.562 inches all ends **Opening Pressure Setting:** 1900.0 pounds per square inch Material: Stainless steel Media For Which Designed: Hydraulic fluid, petroleum base single response **Surface Treatment: Passivate Style Designator:** Straight through note: to be used for valve bodies of one section only. **Thread Series Designator:** Unf all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-097-8172

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0