NSN 4820-00-103-5909

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-103-5909 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 600.0 pounds per square inch single response **Thread Size:** 0.875 inches all ends Seat Angle: 37.0 degrees all ends **Opening Pressure Setting:** 2.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.625 inches all ends Material: Aluminum alloy seat **Material Specification:** Qq-a-225/6, alloy 2024, t4 federal specification single material response seat Media For Which Designed: Fuel/oil, hydrocarbon 5th response **Style Designator:** Straight thru **Thread Series Designator:** Unjf all ends Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-103-5909

Check Valve - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-p-5315 spec.