NSN 4820-00-104-2021

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-104-2021

Dina Cina Assammadatada				
Pipe Size Accommodated:				
0.250 inches all ends				
Thread Direction:				
Right-hand all ends				
Flow Control Device:				
Poppet				
Bonnet Type:				
Inside spring				
Bonnet Attachment Method:				
Integral				
Disk Loading Method:				
Spring				
Maximum Operating Temp:				
250.0 degrees fahrenheit single response				
Connection Style:				
Plain, optional en (pipe) all ends				
Valve Operation Method:				
Automatic				
Connection Type:				
Threaded internal pipe all ends				
Features Provided:				
Valve stem lock shield and bonnet packing and pressure tight outlet side				
Maximum Operating Pressure:				
450.0 pounds per square inch single response				
Thread Size:				
0.250 inches all ends				
Opening Pressure Setting:				
360.0 pounds per square inch				
Material:				
Aluminum alloy body				
Media For Which Designed:				
Water-oil-gas single response				
Surface Treatment:				
Anodize				
Surface Treatment Specification:				
Mil-a-8625, type 2 military specification single treatment response				
Style Designator:				
Angle				
Thread Series Designator:				
Npt all ends				
Shelf Life:				
N/a				

NSN 4820-00-104-2021

Safety Relief Valve - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.