

View Online at <https://aerobasegroup.com/nsn/4820-00-104-8746>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

1.0 cubic feet per minute

**Maximum Operating Temp:**

300.0 degrees fahrenheit 1st response

**Connection Style:**

External seat for gasket seal (boss) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external boss 1st end

**Maximum Operating Pressure:**

200.0 pounds per square inch 3rd response

**Thread Size:**

0.437 inches 1st end

**Opening Pressure Setting:**

7.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Material:**

Aluminum alloy 2024 and rubber butadiene-acrylonitrile class nbr flow control device

**Material Specification:**

Qq-a-225/6 federal specification single material response and mil-r-7362, type 2 federal specification 1st material response flow control device

**Media For Which Designed:**

Air 1st response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Straight through w/baffle

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.