NSN 4820-00-105-0213

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-105-0213

| Pipe Size Accommodated: |
|--|
| 0.250 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Integral |
| Disk Loading Method: |
| Spring |
| Valve Discharge Flow Rate: |
| 3.0 cubic feet per minute |
| Maximum Operating Temp: |
| 125.0 degrees fahrenheit single response |
| End Application: |
| Grumman aircraft, model a10 |
| Connection Style: |
| Plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external pipe 1st end |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch single response |
| Thread Size: |
| 0.250 inches 1st end |
| Opening Pressure Setting: |
| 155.0 pounds per square inch |
| Material: |
| Copper alloy body |
| Media For Which Designed: |
| Air single response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-00-105-0213

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0