NSN 4820-00-105-3143

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-105-3143

Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Renewable Seat Ring Type:
Pressed-in
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded external pipe 1st end
Features Provided:
Bonnet packing
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 12 1st end
12 1st end
12 1st end Maximum Operating Pressure:
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size:
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material:
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator:
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator: Straight thru
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator: Straight thru Thread Series Designator:
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator: Straight thru Thread Series Designator: Un 1st end
Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator: Straight thru Thread Series Designator: Un 1st end Shelf Life:
Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator: Straight thru Thread Series Designator: Un 1st end Shelf Life: N/a
Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator: Straight thru Thread Series Designator: Un 1st end Shelf Life: N/a
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator: Straight thru Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:
12 1st end Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 2.750 inches 1st end Material: Steel comp 316 stem Style Designator: Straight thru Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: