

View Online at <https://aerobasegroup.com/nsn/4820-00-113-6014>

Thread Class:

3b all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

225.0 degrees fahrenheit single response

Connection Style:

Gasket sea (boss) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss all ends

Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Opening Pressure Setting:

1000.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.500 inches all ends

Material:

Stainless steel flow control device

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Angle

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.