

View Online at <https://aerobasegroup.com/nsn/4820-00-113-6014>

**Thread Class:**

3b all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Poppet

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Integral

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

225.0 degrees fahrenheit single response

**Connection Style:**

Gasket sea (boss) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded internal boss all ends

**Features Provided:**

Valve stem lock shield and bonnet packing and pressure tight outlet side

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

0.750 inches all ends

**Opening Pressure Setting:**

1000.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.500 inches all ends

**Material:**

Stainless steel flow control device

**Media For Which Designed:**

Water-oil-gas single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Angle

**Thread Series Designator:**

Unjf all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.