NSN 4820-00-114-2920

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-114-2920 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 350.0 degrees fahrenheit single response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 600.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends Seat Angle: 12.0 degrees all ends Material: Aluminum alloy **Material Specification:** Qq-a-225/6, alloy 2024, t351 federal specification all material responses Media For Which Designed: Water-oil-gas single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:**

Unif all ends
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-00-114-2920

Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.