NSN 4820-00-114-2920

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-114-2920

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

350.0 degrees fahrenheit single response

Connection Style:

Flareless all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

600.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Seat Angle:

12.0 degrees all ends

Material:

Aluminum alloy

Material Specification:

Qq-a-225/6, alloy 2024, t351 federal specification all material responses

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-114-2920

Check Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.

