## NSN 4820-00-119-3716

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-119-3716

Pipe Size Accommodated:
0.750 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded internal pipe all ends
Features Provided:
Valve stem lock shield
Adjustable Pressure Range:
+100.0 to 1500.0 pounds per square inch
Thread Size:
0.750 inches all ends
Material:
Steel body
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Reference Number Differentiating Characteristics:
As differentiated by valve size and type ofpressure adjustment
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-119-3716

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0