## NSN 4820-00-122-2361

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-122-2361

Pipe Size Accommodated:
1.000 inches 2nd end
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Connection Style:
Plain (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Mounting Facility:
Threaded fastener
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
12 1st end
<b>Maximum Operating Pressure:</b>
23.0 pounds per square inch single response
Thread Size:
1.625 inches 2nd end
Seat Angle:
45.0 degrees 1st end
Opening Pressure Setting:
20.0 pounds per square inch
Outside Diameter Tube Accommodated:
1.000 inches 1st end
Material:
Aluminum alloy stem
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Style Designator:
Straight thru
Thread Series Designator:
Un 1st end
Shelf Life:
N/a

## NSN 4820-00-122-2361

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0