

View Online at <https://aerobasegroup.com/nsn/4820-00-124-5690>

Pipe Size Accommodated:

0.750 inches all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Piston

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

40.0 gallons per minute

Renewable Seat Ring Type:

Pressed-in

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe all ends

Mounting Facility:

Bracket

Features Provided:

Bonnet packing and pressure tight outlet side

Adjustable Pressure Range:

+1000.0 to 4000.0 pounds per square inch

Maximum Operating Pressure:

4000.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Opening Pressure Setting:

2500.0 pounds per square inch

Special Features:

W/screw adjustment for setting relief pressure

Material:

Steel flow control device

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Anodize

Style Designator:

Straight through note: to be used for valve bodies of one section only.

Thread Series Designator:

Nptf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0