

View Online at <https://aerobasegroup.com/nsn/4820-00-125-3073>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Connection Style:

Gasket seal (boss) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss 2nd end

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Special Features:

2.0 psi valve opening pressure

Material:

Steel comp 304 flow control device and rubber butadiene-acrylonitrile class nbr flow control device and steel comp 303 flow control device

Material Specification:

Aisi 304/sae 30304 assn standard 1st material response flow control device

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.